SONDE IN NYLON

La serie in nylon, disponibile in diametro pari a 3 mm e 4 mm con teste fisse ed intercambiabili, garantisce buona flessibilità, elevata rigidità di introduzione e indeformabilità.

NYLON WIRE PULLERS

The nylon series is available in 3 mm and 4 mm diameters and with fixed or interchangeable heads. It guarantees high flexibility, high stiffness during cable insertion.



Codice *Code*	Descrizione *Description*	Tipologia terminali *Terminal type*	Diametro ø (mm) *Diameter ø (mm)*	Colore *Colour*	Lunghezza (m) *Length (m)*	Conf. (pz) *PHS (pcs)*
SND-N030.05TF	sonda passacavi in nylon ø 3 mm con terminali fissi ø 5 mm, pressati, completa di testa flessibile e anello tirante. *ø 3 mm nylon duct rod with ø 5 mm fixed pressed terminal, with flexible head and pull ring.*	fisso *fixed*	3	bianco RAL9002 *white RAL9002*	5	1/30
SND-N030.10TF					10	1/20
SND-N030.15TF					15	1/10
SND-N030.20TF					20	1/5
SND-N030.25TF					25	1/5
SND-N030.30TF					30	1/5
SND-N030.05TI	sonda passacavi in nylon ø 3 mm con terminali intercambiabili M5 ø 6 mm, completa di testa flessibile (SND-128.ACC) e anello tirante (SND-131.ACC). *ø 3 mm nylon duct rod with M5 ø 6 mm interchangeable terminals, with flexible head and pull ring.*	filettato *threaded*	3	bianco RAL9002 *white RAL9002*	5	1/30
SND-N030.10TI					10	1/20
SND-N030.15TI					15	1/10
SND-N030.20TI					20	1/5
SND-N030.25TI					25	1/5
SND-N030.30TI					30	1/5
SND-N040.05TF	sonda passacavi in nylon ø 4 mm con terminali fissi ø 6 mm, pressati, completa di testa flessibile e anello tirante. *ø 4 mm nylon duct rod with ø 6 mm fixed pressed terminal, with flexible head and pull ring.*	fisso *fixed*	4	nero RAL9017 *black RAL9017*	5	1/30
SND-N040.10TF					10	1/20
SND-N040.15TF					15	1/10
SND-N040.20TF					20	1/5
SND-N040.25TF					25	1/5
SND-N040.30TF					30	1/5
SND-N040.05TI	sonda passacavi in nylon ø 4 mm con terminali intercambiabili M5 ø 6 mm, completa di testa flessibile (SND-128.ACC) e anello tirante (SND-131.ACC). *ø 4 mm nylon duct rod with M5 ø 6 mm interchangeable terminals, with flexible head and pull ring.*	filettato *threaded*	4	nero RAL9017 *black RAL9017*	5	1/30
SND-N040.10TI					10	1/20
SND-N040.15TI					15	1/10
SND-N040.20TI					20	1/5
SND-N040.25TI					25	1/5
SND-N040.30TI					30	1/5

ACCESSORI PER SONDE IN NYLON CON TERMINALI INTERCAMBIABILI M5 E SONDE IN POLIESTERE Ø 4,2 mm

ACCESSORIES FOR NYLON DUCT RODS WITH INTERCHANGEABLE M5 TERMINALS AND Ø 4.2 mm POLYESTER DUCT RODS

Codice / *Code*	Descrizione / *Description*	Conf. (pz) - *PHS (pcs)*	
SND-127.ACC	testa flex con rotella / *flex head with wheel*	1/10	
SND-128.ACC	testa flex con asola 4,8x3mm / *flex head with hole 4.8x3mm*	1/10	
SND-128L.ACC	testa flex con asola 8,5x3mm / *flex head with hole 8.5x3mm*	1/10	
SND-128LL.ACC	testa flex con asola 8,5x3mm e fresa / *flex head with hole 8.5x3mm and miller*	1/10	
SND-129.ACC	testa flex guida curva ø 6 mm / *flex head, bended guide ø 6 mm*	1/10	
SND-131.ACC	terminale con asola 6,5x3 mm / *terminal with hole 6.5x3 mm*	1/10	
SND-131L.ACC	terminale con asola 10x3 mm / *terminal with hole 10x3 mm*	1/10	
SND-133.ACC	giunto accoppiamento fisso / *joint fixed coupling*	1/10	
SND-134.ACC	testa flex anello piatto ø 8 mm / *flex head, flat eyelet ø 8 mm*	1/10	
SND-140.ACC	testa flex ad asola in corda inox / *flex head with eyelet in steel rope*	1/10	
SND-868.ACC	testa flex guida curve ø 10 mm / *flex head, bended guide ø 10 mm*	1/10	
SND-869.ACC	tirante 32x10x6 con foro 6,5 / *32x10x6 tension rod with 6.5 hole*	1/10	